

CONCRETE PRODUCTS

W&J CHAMBERS LTD 91 GLENSHANE RD, DRUMAHOE, CO. LONDONDERRY, BT47 3SG

T +44(0)28 71301239 E headoffice@wjchambers.com

V.A.T Reg. No. GB 253 5059 67 IR. V.A.T Reg. No. IE 7404 637M

Company Reg. No. NI 28587

DECLARATION OF PERFORMANCE (DOP)



CATEGORY | AGGREGATE CONCRETE MASONRY UNITS NO. 009

1. Unique identification of Product type:

Description	CharacteristicStrength N/mm²	Dimensions (Length - Width - Height)mm		
	10N/mm² (Capped)	Length	Width	Height
6x6 Block	W LOAD H	440	140	140

2. Type batch or serial number or any other element allowing identification of the construction product as required under Article 11 (4) of the CPR:

The production details are traceable by the delivery note

3. Intended use/s:

IS EN 771-3 2011 & BS EN 771-3 2011 - Aggregate Concrete Masonry Units intended for use in load bearing or non-load bearing buildings and civil engineering end uses

4. Manufacturer:

W & J Chambers Ltd, 91 Glenshane Road, Drumahoe, Co Londonderry BT47 3SG

5. Authorised representative:

Mr. Gordon Chambers Director of W&J Chambers LTD

6. System of AVCP:

System 2+

7. Harmonised standard:

EN 771-3 Specification for Masonry units Part 3: Aggregate Concrete Masonry Units (Dense & Lightweight aggregates)

8. Notification certification body:

National standards Authority of Ireland (NSAI) 0050 - CPR - 1056

9. Declared performance:

Essential characteristics	Declared Performance	Harmonised - technical specification	
Dimensional Tolerance	D1	IS EN772-16	
Configuration	Group 1	IS EN 1996-1-1	
Gross Density (Direct Airborne Sound Insulation)	2000 kg/m³	IS EN 772-13	
Compressive Strength (Characteristic)	10.0 N/mm² (Capped)	IS EN 772-1	
Dimensional Stability - Moisture Movement	<0.6mm/m	IS EN 772-14	
Reaction To Fire	Class A1	Based on Commission Decision 200/605 EC - 96/603 EC (Tabulated Value)	
Durability Against Freeze Thaw	Not to be left exposed.	N/A	
Thermal Conductivity	1.10 W/mK(10, dry, unit, S1)	IS EN 1745 Annex A (Tabulated Value)	
Water Absorption	<10g/m²s	IS EN 772-11	
Shear Bond Strength	0,15N/mm²	IS EN 998-2 (Tabulated Value)	
Water Vapour Permeability	5/15 <i>u</i>	IS EN 1745 Annex A (Tabulated Value)	
*Dangerous Substances	NPD	See note	

Information on dangerous substances will only be given when and where required in the appropriate form. See Annex ZA.3 of EN 771-3

Signed for and on behalf of W& J Chambers Ltd by:

Place & date of issue:

Drumahoe 26.11.20

